



TWMND

N-type Half-cell
Bifacial Module (72)

72HD565-585W

High Power Output
Low LCOE




Maximum Power
585W+



www.tw-solar.com



Learn More

DRAWINGS (Unit: mm)

ELECTRICAL CHARACTERISTICS (STC)

Module Type: TWMND-72HDXXX

Maximum Power: P_{max} [W]	565	570	575	580	585
Open Circuit Voltage: V_{oc} [V]	51.04	51.24	51.44	51.64	51.84
Short Circuit Current: I_{sc} [A]	14.17	14.21	14.25	14.29	14.33
Voltage at Maximum Power: V_{mp} [V]	42.68	42.88	43.08	43.28	43.48
Current at Maximum Power: I_{mp} [A]	13.24	13.29	13.35	13.40	13.46
Module Efficiency: η [%]	21.9	22.1	22.3	22.5	22.6

ELECTRICAL CHARACTERISTICS (NMOT)

Maximum Power: P_{max} [W]	424.8	428.6	432.4	436.1	439.9
Open Circuit Voltage: V_{oc} [V]	48.48	48.67	48.86	49.05	49.24
Short Circuit Current: I_{sc} [A]	11.47	11.52	11.56	11.60	11.63
Voltage at Maximum Power: V_{mp} [V]	39.89	39.95	40.00	40.19	40.37
Current at Maximum Power: I_{mp} [A]	10.63	10.70	10.78	10.85	10.90

* STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass1.5, Measuring Tolerance: ±3%

* NMOT: Irradiance 800W/m², Ambient Temperature 20°C, Air Mass1.5, Wind Speed 1m/s

ELECTRICAL CHARACTERISTICS (Rear Power Gain)

5%	Maximum Power: $P_{max}[W]$	593.3	598.5	603.8	609.0	614.3
	Module Efficiency: η [%]	23.0	23.2	23.4	23.6	23.8
15%	Maximum Power: $P_{max}[W]$	649.8	655.5	661.3	667.0	672.8
	Module Efficiency: η [%]	25.2	25.4	25.6	25.8	26.0
25%	Maximum Power: $P_{max}[W]$	706.3	712.5	718.8	725.0	731.3
	Module Efficiency: η [%]	27.3	27.6	27.8	28.1	28.3

TEMPERATURE PARAMETERS


Temperature Coefficient (Pmax)	-0.30%/°C
Temperature Coefficient (Voc)	-0.25%/°C
Temperature Coefficient (Isc)	+0.046%/°C
NMOT	45±2°C

MAXIMUM RATINGS


Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Power Output Tolerance	0~+5W
Maximum Bifaciality	80±5%

MECHANICAL PARAMETERS

Cells	TNC (N Type Monocrystalline Cell)
Cell Orientation	144[6X24]
Dimension	2278±2X1134±2X30mm
Weight	31.5kg
Front Glass	2.0mm high transmittance, AR semi-tempered glass
Rear Glass	2.0mm semi-tempered glass
Frame	Anodized aluminum alloy frame
Junction Box	IP68, 3 diodes
Output Cable	4.0mm ²
Cable Length	+400mm, -200mm, length can be customized
Wind/Snow Load	2400Pa/5400Pa
Packaging	36pcs per pallet, 720pcs per 40'HC

WARRANTY

I-V CURVE



CERTIFICATIONS

Quality Management System and Product Certification

ISO 9001:2015 / quality management system

ISO 14001:2015 / environmental management system

ISO 45001:2018 / occupation health safety management system

ISO 50001:2011 / energy management system

IEC TS 62941—2016 / PV industry quality management system

IEC 61215/61730, IEC 62804(PID), IEC 61701(Salt)

IEC 62716 (Ammonia), IEC 60068-2-68(Sand)



Email: sales@tongwei.com

Website: www.tongwei.com.cn

Add: 888 Changning Avenue, High-tech Zone, Hefei City, Anhui Province

Declaration: With the technical progress and product updates, there exists a deviation between the technical parameter of the TW Solar's future products and the technical parameter in this specification. The TW Solar reserves the right to adjust the technical parameter at any time without notifying the customers. TW Solar reserves the final right of interpretation. (20230802 A2)