

Rackwall 10.5 51.2V200AH



Model:
LIO 10.5-IP20



1C
continuous charge
and discharge

Safety

- Long life type prismatic LiFePO4 cells, suitable for energy storage application.
- Low voltage system, safety for application.
- Cell certification: IEC62619, UL1973, UL9540A, ROHS.
- Battery certification: UN38.3, MSDS, CE

Scalability

- Parallel support for more energy.
- Communication compatible with the major inverter manufacturers, Change different inverter protocol by LCD.

Design

- Standard 19" rack design.
- Flexible and easily installation, rack mounted.
- -20~+55°C widely temperature range.
- 4.3" touch LCD screen.
- Quick Lock and Press-to- Release Terminals.
- Maintenance free.

Battery Management System

- Independent protection for charge and discharge.
- SOC, Alarm, Run display and PC software for detailed operation.
- OVP, LVP, OCP, OTP, LTP, Short-circuit protection.
- RS485,CAN communication port for inverter and Link in & out for battery to battery communication.

Technical Data Sheet

| Model | LIO 10.5-IP20 |
|---------------------------------|--|
| Nominal Voltage [V] | 51.2 |
| Nominal Capacity [Ah] | 200 |
| Total Energy [Wh] | 10240 |
| Dimension (W*D*H, mm) | 442*550*250 |
| Weight [Kg] | 83.0 |
| Max. Charging Current [A] | 200 |
| Max. Discharging Current [A] | 200 |
| Pulse Discharge Current | 240A @2S |
| Charging Voltage [V] | 55.2-57.6 |
| End of Discharge Voltage [V] | 48 |
| Operation Humidity | 0-95% RH (No condensing) |
| Operating Temperature Range | Charge: 0 ~ +55°C; Discharge: -20 ~ +55°C |
| Cycle Life ⁽¹⁾ | >6000 |
| Designed Calendar Life | 10 Years |
| Communication interface | For inverter : RS485, CAN For battery to battery: LINK-IN, LINK-OUT |
| Protection | Over voltage, Low voltage, Over current, Over Temperature, Low Temperature, Short circuit |
| Parallel Support ⁽²⁾ | Yes, Max. 15 Sets |
| Series Support | Not support |

Note:

(1) 25°C, 0.5C /1C , 90%DOD to 80% of initial capacity.

(2) For parallel connection, refer to user manual.

VERSION : MAY 2025